

## **VETERAANIT MARRASKUU 2025**



Oil Pattern Distance Forward Oil Total Tank Configuration

> 1500 · 1350 · 1200 ·

40 11.04 mL Multi Tank Reverse Brush Drop Reverse Oil Total Tank A Conditioner 36 10.4 mL TERRAIN Oil Per Board Volume Oil Total Tank B Conditioner 40 ul 21.44 mL ICE

25

22

45

8

35

8

25

1     2L     2R     1     14     3     A     37     0.0     0.0     0.0     1480       2     5L     5R     2     14     3     A     62     0.0     3.9     3.9     2480       3     9L     9R     3     18     3     A     69     3.9     11.5     7.6     2760       4     12L     12R     3     18     3     A     51     11.5     19.1     7.6     2040       5     14L     14R     3     18     3     A     39     19.1     26.7     7.6     1560	1 2L 2R 1 14 3 A 37 0.0 0.0 0.0 1480 2 5L 5R 2 14 3 A 62 0.0 3.9 3.9 2480 3 9L 9R 3 18 3 A 69 3.9 11.5 7.6 2760 4 12L 12R 3 18 3 A 51 11.5 19.1 7.6 2040 5 14L 14R 3 18 3 A 39 19.1 26.7 7.6 1560 6 16L 16R 2 22 3 A 18 26.7 32.9 6.2 720		START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
3     9L     9R     3     18     3     A     69     3.9     11.5     7.6     2760       4     12L     12R     3     18     3     A     51     11.5     19.1     7.6     2040       5     14L     14R     3     18     3     A     39     19.1     26.7     7.6     1560	3 9L 9R 3 18 3 A 69 3.9 11.5 7.6 2760 4 12L 12R 3 18 3 A 51 11.5 19.1 7.6 2040 5 14L 14R 3 18 3 A 39 19.1 26.7 7.6 1560 6 16L 16R 2 22 3 A 18 26.7 32.9 6.2 720	1											1480
4 12L 12R 3 18 3 A 51 11.5 19.1 7.6 2040 5 14L 14R 3 18 3 A 39 19.1 26.7 7.6 1560	4 12L 12R 3 18 3 A 51 11.5 19.1 7.6 2040 5 14L 14R 3 18 3 A 39 19.1 26.7 7.6 1560 6 16L 16R 2 22 3 A 18 26.7 32.9 6.2 720	2	5L	5R	2	14	3	Α	62	0.0	3.9	3.9	2480
5 14L 14R 3 18 3 A 39 19.1 26.7 7.6 1560	5 14L 14R 3 18 3 A 39 19.1 26.7 7.6 1560 6 16L 16R 2 22 3 A 18 26.7 32.9 6.2 720	3	9L	9R	3	18	3	Α	69	3.9	11.5	7.6	2760
	6 16L 16R 2 22 3 A 18 26.7 32.9 6.2 720	4	12L	12R	3	18	3	Α	51	11.5	19.1	7.6	2040
6 16L 16R 2 22 3 A 18 26.7 32.9 6.2 720		5	14L	14R	3	18	3	Α	39	19.1	26.7	7.6	1560
	7 2L 2R 0 30 3 A 0 32.9 40.0 7.1 0	6	16L	16R	2	22	3	Α	18	26.7	32.9	6.2	720
7 2L 2R 0 30 3 A 0 32.9 40.0 7.1 0		7	2L	2R	0	30	3	Α	0	32.9	40.0	7.1	0

4			LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
•	2L	2R	0	30	3	В	0	40.0	33.0	-7.0	0
2	12L	12R	3	18	3	В	51	33.0	25.4	-7.6	2040
3	12L	12R	2	18	3	В	34	25.4	20.3	-5.1	1360
4	8L	8R	3	18	3	В	75	20.3	12.7	-7.6	3000
5	8L	8R	2	18	3	В	50	12.7	7.6	-5.1	2000
6	8L	8R	2	18	3	В	50	7.6	2.5	-5.1	2000
7	2L	2R	0	14	3	В	0	2.5	0.0	-2.5	0

Cleaner Ratio Main Mix 24:1 Forward
Cleaner Ratio Back End Mix 33:1 Reverse
Cleaner Ratio Back End Distance 59 Combined
Buffer RPM: 4 = 650 | 3 = 500 | 2 = 300 | 1 = 200

ltem	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
	Outside:Middle		Inside:Middle	Middle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	11.82	1.86	1.07	1.07	1.86	11.82

